

Roblon Multi Strap

Secures buoyancy modules on marine drilling risers, VIV strakes, piggyback blocks and riser fins etc.

Key features

- Easy and quick to install
- Continuous loop
- Does not corrode
- Lighter than steel
- Almost neutrally buoyant
- Aramid and polyester fibers
- No sharp edges
- EAA coating protects the strapped material
- Min. internal circumference 1800 mm
- Multistraps are supplied with cut-outs
- Test certificate supplied
- In-house test facilities available
- Tension devices can be supplied on request



Roblon

Technical data

Min. Breaking strength (kN)	Width (mm) +/- 5%	Thickness (mm) +/- 5%	Standard cut-out width (mm)	Max available cut-out width (mm)	Stiffness (kN *) +/- 10%	Min pin diameter (mm)
30	40	6.0	13	13	1420	25
50	60	6.0	20	24	2365	25
50	90	6.0	25	32	2365	25
75	90	6.0	25	40	3200	30
100	90	6.0	25	25	4570	30
125	90	6.2	25	29	5085	38
200	90	7.0	25	32	6175	55
350	150	7.0	40	45	13400	55

*) The stiffness value increases if the straps are installed multiple times. Please contact Roblon for further details.

Standard colour black. Other colours on request.
Service temperature: -40°C to 70°C.



..... Continuous loop

Single bolt

